

"Welcome to the K Controls e-training course designed to deliver useful "Pneumatic Valve Actuation" application information in small instalments."

To unsubscribe or to register a colleague to receive these documents [Click here](#)

Equipment Protection Levels (EPL's)

BS EN 60079-26:2007 "Equipment with Equipment Protection Level (EPL) Ga

This standard adopts a risk assessment approach for the acceptance of hazardous area equipment as an alternative to the current approach of linking equipment to zones.

Traditionally specific types of protection have been linked to the zone of use e.g. Exn in Zone 2 only. This requires the technician on site to understand the relationship between type of protection and zone of use and it also takes no account of the potential consequences of an explosion, should it occur.

Equipment Protection Levels (EPL's) have been introduced to clearly indicate the inherent ignition risk of equipment irrespective of the type of protection being used.

In future (at a date to be confirmed) product will be marked with additional symbols to designate the equipment protection level.

Gases (Group II)

EPL Ga - Equipment for explosive gas atmospheres, having a "very high" level of protection, which is not a source of ignition in normal operation, expected faults or when subject to rare faults.

EPL Gb - Equipment for explosive gas atmospheres, having a "high" level of protection, which is not a source of ignition in normal operation or when subject to faults that may be expected, though not necessarily on a regular basis.

EPL Gc - Equipment for explosive gas atmospheres, having an "enhanced" level of protection, which is not a source of ignition in normal operation and which may have some additional protection to ensure that it remains inactive as an ignition source in the case of regular expected occurrences (e.g. failure of a lamp)

Dusts (Group III)

EPL Da - Equipment for explosive gas atmospheres, having a "very high" level of protection, which is not a source of ignition in normal operation, expected faults or when subject to rare faults.

EPL Db - Equipment for explosive gas atmospheres, having a "high" level of protection, which is not a source of ignition in normal operation or when subject to faults that may be expected, though not necessarily on a regular basis.

EPL Dc - Equipment for explosive gas atmospheres, having an "enhanced" level of protection, which is not a source of ignition in normal operation and which may have some additional protection to ensure that it remains inactive as an ignition source in the case of regular expected occurrences



E-training

K Controls designs and manufactures valve networking monitoring and control products:

Switchboxes
Control Monitors
Position Transmitters
Corrosion resistant
ATEX certified – gas + dust
High and low temperatures
IP68 for submersion
Low powered solenoids
Remote I/O compatible
AS-interface®
DeviceNet™
PROFIBUS® PA
FOUNDATION™ FIELDBUS
4-20mA + HART®
Wireless solutions
Linear or rotary adaptation

K Controls can also supply your positioner requirements

If you have any questions or comments, would like a colleague to receive this information or you would like the latest list of training documents, please use the contact details below:

K Controls Ltd
2 Crown Way
Crown Business Centre
Horton Road
West Drayton UB7 8HZ
United Kingdom

Phone:
+44 (0)1895 449601

Fax:
+44 (0)207 990 8111

E-mail:
sales@k-controls.co.uk

Web:
www.k-controls.co.uk

Blog:
www.k-controls.info

Visit us:
View a map

There are also equivalent protection levels for coal mining (Group I) EPL Ma and EPL Mb.

For the majority of situations the following traditional relationship of EPL's to Zones is *:

EPL	Zone
Ga	0
Gb	1
Gc	2
Da	20
Db	21
Dc	22

- *1) "Typical" potential consequences of an explosion apply.
- 2) This does not apply to coal mining.

EPL's are the IEC equivalent of the ATEX categories 1G, 2G, 3G for Group II (Surface industry - Gas) and 1D, 2D and 3D for Group III (Surface industry - Dust).

So: Ga = 1G for Zone 0, Gb = 2G for Zone 1 etc.

The EPL notation follows intrinsically safe levels, a, b and c.

E.g. Exia - Ga - Zone 0
Exib - Gb - Zone 1
Exic - Gc - Zone 2

Examples of additional product marking for types of protection used in explosive gas atmospheres : **Ga Ex ia IIC T6** or **Gb Ex d+e IIB T4**

The protection levels for coal mining (Group I) are EPL Ma and EPL Mb.

Trademarks K Controls has used all reasonable resources and efforts to indicate and supply information regarding trademarks used in this document. The absence of a trademark identifier is not a representation that a particular word or technology is not a trademark. All trademarks are property of their respective owners. If we have failed to properly show a trademark, please e-mail us and we will attempt to correct it. The ownership of all trademarks referred to in this document is acknowledged.

Legal Disclaimer This document is written by K Controls for use by its clients. Although we make every reasonable attempt to verify the accuracy of the technical information and advice provided, we can take no responsibility for loss or damage resulting from its interpretation or application. K Controls is not in any way responsible, and has no legal liability, in respect of the contents of any other web site accessed via this document, nor for information provided via that site. All information accessed via links in this document is protected by international copyright laws and may not be reproduced in any form without the explicit written permission of the author. This E-mail and any files transmitted with it are confidential and may be legally privileged. It is intended solely for clients of K Controls Ltd. Any unauthorized recipient should advise K Controls immediately of the error.

Copyright K Controls Ltd 2010 - All rights reserved.