

VALVE POSITIONER ENQUIRY FORM		
How to use this form.		
a	Print the form.	
b	Place a tick or comment against the features you require	
c	Fax a copy to +44 (0)1895 448586	
d	Alternatively scan and email a copy to sales@k-controls.co.uk	
1.0	Customer details	
1.1	Name	
1.2	Company	
1.3	Email address	
1.4	Telephone number	
2.0	<b>Control or communication signal:</b>	
2.1	3-15 psi	<input type="checkbox"/>
2.2	4-20mA	<input type="checkbox"/>
2.3	4-20mA + HART	<input type="checkbox"/>
2.4	Profibus PA	<input type="checkbox"/>
2.5	Foundation Fieldbus	<input type="checkbox"/>
3.0	<b>Feedback or communication signal:</b>	
3.1	Limit switches only (Please specify type)	
3.2	Potentiometer + Limit switches (Please specify type)	
3.3	4-20mA + Limit switches (Please specify type)	
3.4	Potentiometer - no switches	<input type="checkbox"/>
3.5	4-20mA - no switches	<input type="checkbox"/>
3.6	4-20mA + HART	<input type="checkbox"/>
3.7	Profibus PA	<input type="checkbox"/>
3.8	Foundation Fieldbus	<input type="checkbox"/>
4.0	<b>Pressure Gauges:</b>	
4.1	No gauges	<input type="checkbox"/>
4.2	Pressure gauges required	<input type="checkbox"/>
5.0	<b>Alarms:</b>	
5.1	Alarms are not required	<input type="checkbox"/>
5.2	Specific alarms are required from the positioner (please specify)	
6.0	<b>Actuator type:</b>	
6.1	Rotary 90 degrees	<input type="checkbox"/>
6.2	Rotary other (Please define rotation)	<input type="checkbox"/>
6.3	Linear (Please define stroke)	<input type="checkbox"/>
6.4	Single acting	<input type="checkbox"/>
6.5	Double acting	<input type="checkbox"/>
6.6	Please specify the make and size of actuator	
7.0	<b>Failure mode on signal failure:</b>	
7.1	Not important	<input type="checkbox"/>

7.2	Positioner freezes at the current value should the control input signal fail	<input type="checkbox"/>
7.3	Positioner freezes at the current value should the supply pressure fall below a set level	<input type="checkbox"/>
8.0	<b>Calibration:</b>	
8.1	Manual calibration	<input type="checkbox"/>
8.2	Auto calibration required	<input type="checkbox"/>
9.0	<b>Enclosure:</b>	
9.1	Engineered plastic	<input type="checkbox"/>
9.2	Coated aluminium	<input type="checkbox"/>
9.3	Stainless steel	<input type="checkbox"/>
10.0	<b>Ingress Protection:</b>	
10.1	Not important	<input type="checkbox"/>
10.2	IP56 or better	<input type="checkbox"/>
10.3	IP65 or better	<input type="checkbox"/>
10.4	IP67 or better	<input type="checkbox"/>
10.5	Other (Please specify)	
11.0	<b>Hazardous areas:</b>	
11.1	Non hazardous area	<input type="checkbox"/>
11.2	Hazardous area - Exi protection	<input type="checkbox"/>
11.3	Hazardous area - Exd protection	<input type="checkbox"/>
11.4	Hazardous area - Exn protection	<input type="checkbox"/>
11.5	Zone - 0, 1 or 2	
11.6	Gas or dust group - IIA, IIB or IIC	
11.7	Temperature class (T6 - T85°C)	
12.0	<b>Ambient temperature:</b>	
12.1	Ambient temperature is in the range -20 to +40 degrees C.	<input type="checkbox"/>
12.2	Ambient temperature range (please specify)	
13.0	<b>Vibration:</b>	
13.1	No vibration	<input type="checkbox"/>
13.2	Vibration is likely to be significant	<input type="checkbox"/>
14.0	<b>Air quality:</b>	
14.1	Instrument quality	<input type="checkbox"/>
14.2	Poor	<input type="checkbox"/>
15.0	<b>Other features:</b>	
5.1	Partial stroke testing function required	<input type="checkbox"/>
15.2	Defined safety integrity level (SIL) required (please specify)	
15.3	Operation with natural gas	<input type="checkbox"/>
15.4	Valve diagnostics required (please specify)	
15.5	Positioner self diagnostics required	<input type="checkbox"/>
15.6	Positioner to be mounted remotely from the actuator.	<input type="checkbox"/>
16.0	Quantity required	
17.0	Delivery required	

